

**WHAT IS CLAIMED IS:**

1. A system, comprising:

5 a first node of a distributed store comprising a primary state of session data configured for access by a plurality of application servers, wherein the session data comprises a plurality of attributes;

another node comprising a back-up instance of the primary state;

10 wherein the system is configured to:

compare the primary state to a benchmark of the primary state to generate  
a subset of the attributes of the session data that have been  
15 modified in the primary state; and

synchronize the back-up instance of the primary state with the primary  
state using the subset of the attributes of the session data.

20 2. The system as recited in claim 1, wherein, to compare the primary state to the benchmark of the primary state, the system is further configured to perform binary differencing of a binary representation of the primary state and a binary representation of the benchmark of the primary state to determine the modified attributes.

25 3. The system as recited in claim 2, wherein, to perform binary differencing, one or more portions of the binary representation of the primary state are compared to corresponding portions of the binary representation of the benchmark of the primary state to determine the modified attributes.

30 4. The system as recited in claim 1, wherein, to compare the primary state to

a benchmark of the primary state, the system is further configured to perform object graph differencing of an object graph representation of the primary state and an object graph representation of the benchmark of the primary state to determine the modified attributes.

5           5.       The system as recited in claim 4, wherein the attributes comprise objects organized according to an object graph representation, wherein, to perform object graph differencing, one or more objects in the object graph representation of the primary state are compared to corresponding instances of objects in an object graph representation of the benchmark of the primary state to identify the modified attributes of the primary state.

10

6.       The system as recited in claim 1, wherein the another node comprising a back-up instance of the primary state is another node of the distributed store.

7.       A system comprising:

15

a distributed store node comprising a primary state of session data configured for access by a plurality of application servers, wherein the session data comprises a plurality of attributes;

20

another node comprising a back-up instance of the primary state;

wherein the system is configured to:

25

generate a set of the plurality of attributes that are mutable attributes for use in synchronizing the back-up instance of the primary state with the primary state; and

30

synchronize the back-up instance of the primary state with the primary state according to the generated set of the mutable attributes of the session data.

8. The system as recited in claim 7, wherein the system is further configured to compare the set of the mutable attributes to a benchmark of the primary state to determine a subset of the attributes of the session data that have been modified in the primary state.

9. The system as recited in claim 8, wherein, to compare the primary state to a benchmark of the primary state, the system is further configured to perform binary differencing of a binary representation of the primary state and a binary representation of the benchmark of the primary state to locate the modified attributes.

10. The system as recited in claim 8, wherein, to compare the primary state to a benchmark of the primary state, the system is further configured to perform object graph differencing of an object graph representation of the primary state and an object graph representation of the benchmark of the primary state to locate the modified attributes.

11. A system comprising:  
a distributed store node comprising a primary state of session data configured for access by a plurality of application servers, wherein the session data comprises a plurality of attributes;

another node comprising another instance of the primary state;  
means for determining a set of the attributes of the session data that differ between the primary state and the other instance of the primary state; and

means for synchronizing the other instance of the primary state with the primary state using the set of the attributes of the session data that differ between the primary state and the other instance of the primary state.

12. The system as recited in claim 11, wherein the means for determining a set of the attributes comprise comparing the primary state to a benchmark of the primary state to determine attributes of the session data that have been modified in the primary state.

13. The system as recited in claim 12, wherein, to compare the primary state to a benchmark of the primary state, the means further comprise performing binary differencing of a binary representation of the primary state and a binary representation of the benchmark of the primary state to locate the modified attributes.

14. The system as recited in claim 12, wherein, to compare the primary state to a benchmark of the primary state, the means further comprise performing object graph differencing of an object graph representation of the primary state and an object graph representation of the benchmark of the primary state to locate the modified attributes.

15. A method comprising:  
  
providing access to a primary state of session data comprised by a distributed store node to a plurality of application servers, wherein the session data comprises a plurality of attributes;

comparing the primary state to a benchmark of the primary state to generate a subset of the attributes of the session data that have been modified in the primary state; and

synchronizing the another instance of the primary state comprised by another node with the primary state using the subset of the attributes of the session data.

16. The method as recited in claim 15, wherein said comparing the primary

state to a benchmark of the primary state comprises performing binary differencing of a binary representation of the primary state and a binary representation of the benchmark of the primary state to determine the modified attributes.

5           17.     The method as recited in claim 16, wherein performing binary differencing comprises comparing one or more portions of the binary representation of the primary state to corresponding portions of the binary representation of the benchmark of the primary state to determine the modified attributes.

10           18.     The method as recited in claim 15, wherein said comparing the primary state to a benchmark of the primary state comprises performing object graph differencing of an object graph representation of the primary state and an object graph representation of the benchmark of the primary state to determine the modified attributes.

15           19.     The method as recited in claim 18, wherein the attributes comprise objects organized according to an object graph representation, wherein performing object graph differencing comprises comparing one or more objects in the object graph representation of the primary state to corresponding instances of objects in an object graph representation of the benchmark of the primary state to identify the modified attributes of  
20     the primary state.

          20.     The method as recited in claim 15, wherein the other instance of the primary state is a backup of the primary state.

25           21.     An article of manufacture comprising software instructions executable to implement:

          providing access to a primary state of session data comprised by a distributed  
30           store node to a plurality of application servers, wherein the session data

comprises a plurality of attributes;

comparing the primary state to a benchmark of the primary state to generate a  
subset of the attributes of the session data that have been modified in the  
primary state; and

synchronizing the another instance of the primary state comprised by another node  
with the primary state using the subset of the attributes of the session data.

22. The article of manufacture as recited in claim 21, wherein said comparing  
the primary state to a benchmark of the primary state comprises performing binary  
differencing of a binary representation of the primary state and a binary representation of  
the benchmark of the primary state to determine the modified attributes.

23. The article of manufacture as recited in claim 22, wherein said performing  
binary differencing comprises comparing one or more portions of the binary  
representation of the primary state to corresponding portions of the binary representation  
of the benchmark of the primary state to determine the modified attributes.

24. The article of manufacture as recited in claim 21, wherein said comparing  
the primary state to a benchmark of the primary state comprises performing object graph  
differencing of an object graph representation of the primary state and an object graph  
representation of the benchmark of the primary state to determine the modified attributes.

25. The article of manufacture as recited in claim 24, wherein the attributes  
comprise objects organized according to an object graph representation, wherein said  
performing object graph differencing comprises comparing one or more objects in the  
object graph representation of the primary state to corresponding instances of objects in  
an object graph representation of the benchmark of the primary state to identify the  
modified attributes of the primary state.

26. The article of manufacture as recited in claim 21, wherein the other instance of the primary state is a backup of the primary state.

2025-04-23 14:23:00